

NEW

Power To Go

Mobile printing with the EOS1-24V



we identify more

Whether in production or in the warehouse – often printing needs to take place in places where neither energy nor data is available.












The EOS 1-24V doesn't need a wall socket or a network connection.

- Energy supply by battery pack with an output of approx. 5.000 labels (110 x 68mm with 15% density)
- Data transfer via WLAN, Nano Bluetooth or USB stick
- Data input via keyboard in stand-alone operation or via barcode entry

The battery pack is mounted underneath the printer. The EOS1-24V is provided with a connector for the battery pack. For charging the battery pack is connected to mains voltage, printing is still possible during the charging process. Charging time approx. 4 hours.



Delivery program

	Part no.	Hardware	dpi
	5965101.600 5965102.600	EOS1 - 24V with tear-off plate Label printer EOS1 / 200 B Label printer EOS1 / 300 B	
	5965110.600 5965112.600	EOS1 - 24V with cutter Label printer EOS1 / 200 C Label printer EOS1 / 300 C	
	Part no.	Accessories	
	5966218.001	Print roller DR4-25	
	5966219.001	Print roller DR4-50	
	5965586	External roll retainer EOS	
	5965520	Cutter EOS1 C	
	5542640	Battery pack EOS1 - 24V	
	5901626	Standard keyboard USB German version	
	5906179	USB Memory stick	
	5906225	WLAN USB stick 54 Mbps	
	5906226	Nano Bluetooth USB Adapter V2.1	

Technical data

EOS1 - 24V	
Input voltage	16 - 28 VDC - for all further data please refer to EOS1
Battery pack	
Battery	NiMH (Nickel-Metal Hydride)
Nominal voltage	18 V
Nominal current	2,5 A (max. 30 A at 30 ms)
Capacity/Consumption	4 Ah / 72 Wh
Print capacity	about 5000 labels 110 x 68 mm at density of 15%
Charging time	approx. 4 h
Charging cycles	> 500
Indicators	green Battery pack is connected to the power supply
	red Battery charge
	yellow Battery error
	green blinking Battery charge about 70 - 100%
	yellow blinking Battery charge about 30 - 70%
	red blinking Battery charge < 30%
Power supply	100 – 240 VAC 50/60 Hz
Temperature/ Humidity	Operation + 5 - 40°C / 10 - 85% not condensing Storage + 0 - 60°C / 20 - 80% not condensing Transport -25 - 60°C / 20 - 80% not condensing
Approvals	CE, FCC class A, CB, CCC, UL

All specifications about delivery, design and technical data are given to the best of our current knowledge and are subject to change without prior notice. **For more information go to www.cab.de**